



**Size:**  
1.25 x 0.80 x 0.40 inches  
(31.8 x 20.3 x 10.2 mm)

**Applications:**

- Medical Equipment
- Telecom/Datacom
- Industry Control Systems
- Measurement Equipment
- Semiconductor Equipment
- PV Power Systems
- IGBT Gate Drivers

**FEATURES**

- 2µA Patient Leakage Current
- Single & Dual Outputs
- Under Voltage Protection
- High Efficiency up to 89%
- 4:1 Wide Input Voltage Ranges
- Built-in EMI Class A Filter
- Low Stand-by Power Consumption
- 6 Watts Output Power
- Reinforced Insulation for 250VAC Working Voltage
- Clearance and Creepage Distance: 8.0mm/2MOPP
- 5000VAC Input to Output 2MOPP Isolation
- Short Circuit, Over Voltage, and Over Load Protection
- CE Marked
- Compliant to RoHS II & REACH
- ANSI/AAMI ES60601-1, EN60601-1, IEC60601-1 3<sup>rd</sup> Edition, UL60950-1, EN60950-1, & IEC60950-1 Safety Approvals
- Optional Remote ON/OFF Control and Trim Pin

**DESCRIPTION**

The DCMPPW06 series of medical DC/DC power converters provides 6 Watts of output power in a 1.25" x 0.80" x 0.40" DIP package. This series consists of single and dual output models with 4:1 wide input voltage ranges of 9-36VDC and 18-75VDC. Some features include high efficiency up to 89%, 5000VAC I/O (2 MOPP) isolation, and low stand-by power consumption. These converters are also protected against under voltage, short circuit, over voltage, and over load conditions. All models are RoHS compliant and have ANSI/AAMI ES60601-1, EN60601-1, IEC60601-1 3<sup>rd</sup> Edition, UL60950-1, EN60950-1, and IEC60950-1 safety approvals. Remote ON/OFF and Trim functions are also available for this series.

**MODEL SELECTION TABLE**

**SINGLE OUTPUT MODELS**

Model Number <sup>(1)</sup>	Input Voltage	Output Voltage	Output Current	Output Ripple & Noise	No Load Input Current	Output Power	Efficiency	Maximum Capacitive Load
DCMPPW06-24S33x	24VDC (9 - 36 VDC)	3.3 VDC	1800mA	30mVp-p	6mA	6W	83%	2100µF
DCMPPW06-24S05x		5 VDC	1200mA	30mVp-p	6mA	6W	86%	1500µF
DCMPPW06-24S12x		12 VDC	500mA	40mVp-p	6mA	6W	89%	260µF
DCMPPW06-24S15x		15 VDC	400mA	40mVp-p	6mA	6W	89%	210µF
DCMPPW06-24S24x		24 VDC	250mA	50mVp-p	6mA	6W	88.5%	75µF
DCMPPW06-48S33x	48 VDC (18 - 75 VDC)	3.3 VDC	1800mA	30mVp-p	4mA	6W	82.5%	2100µF
DCMPPW06-48S05x		5 VDC	1200mA	30mVp-p	4mA	6W	86.5%	1500µF
DCMPPW06-48S12x		12 VDC	500mA	40mVp-p	4mA	6W	88%	260µF
DCMPPW06-48S15x		15 VDC	400mA	40mVp-p	4mA	6W	88.5%	210µF
DCMPPW06-48S24x		24 VDC	250mA	50mVp-p	4mA	6W	88%	75µF

**DUAL OUTPUT MODELS**

Model Number <sup>(1)</sup>	Input Voltage	Output Voltage	Output Current	Output Ripple & Noise	No Load Input Current	Output Power	Efficiency	Maximum Capacitive Load
DCMPPW06-24D05x	24 VDC (9 - 36 VDC)	±5 VDC	±600mA	30mVp-p	6mA	6W	85%	±860µF
DCMPPW06-24D12x		±12 VDC	±250mA	40mVp-p	6mA	6W	88.5%	±150µF
DCMPPW06-24D15x		±15 VDC	±200mA	40mVp-p	6mA	6W	88.5%	±110µF
DCMPPW06-48D05x	48 VDC (18 - 75 VDC)	±5 VDC	±600mA	30mVp-p	4mA	6W	85%	±860µF
DCMPPW06-48D12x		±12 VDC	±250mA	40mVp-p	4mA	6W	88%	±150µF
DCMPPW06-48D15x		±15 VDC	±200mA	40mVp-p	4mA	6W	87%	±110µF

**TECHNICAL SPECIFICATIONS: DCMPPW06 SERIES**

All specifications are based on 25°C, Nominal Input Voltage, and Maximum Output Current unless otherwise noted.  
We reserve the right to change specifications based on technological advances.

SPECIFICATION	TEST CONDITIONS		Min	Typ	Max	Unit	
<b>INPUT SPECIFICATIONS</b>							
Input Voltage Range	24VDC nominal input models		9	24	36	VDC	
	48VDC nominal input models		18	48	75		
Start-Up Voltage	24VDC nominal input models				9	VDC	
	48VDC nominal input models				18		
Shutdown Voltage	24VDC nominal input models			8		VDC	
	48VDC nominal input models			16			
Input Surge Voltage (3sec, max.)	24VDC nominal input models				50	VDC	
	48VDC nominal input models				100		
Input Current	No Load		See Table				
Input Filter			Pi type				
Remote ON/OFF Control (Only for "B" type pin connection models)	Referenced to -INPUT pin	DC/DC ON	Open or 0 ~ 1.2VDC				
		DC/DC OFF	2.2 ~ 12 VDC				
Input Current of CTRL Pin	Nominal Vin		-0.5		1	mA	
Remote OFF Input Current	Nominal Vin			2.5		mA	
<b>OUTPUT SPECIFICATIONS</b>							
Output Voltage			See Table				
Voltage Accuracy			-1.0		+1.0	%	
Line Regulation	Low line to high line at full load	Single Output Models	-0.2		+0.2	%	
		Dual Output Models	-0.5		+0.5		
Load Regulation	No load to full load	Single Output Models	-0.2		+0.2	%	
		Dual Output Models	-1.0		+1.0		
Cross Regulation	Asymmetrical load 25%/100% FL	Dual Output Models	-5.0		+5.0	%	
Voltage Adjustability (Only for "B" type pin connection models)	Single Output Models	3.3V, 5V, 12V Output Models	-10		+10	%	
		15V, 24V Output Models	-10		+20		
		Dual Output Models	±5V, ±12V, ±15V Output Models	-10			+10
Output Power			See Table				
Output Current			See Table				
Maximum Capacitive Load	Minimum input and constant resistive load		See Table				
Ripple & Noise (20MHz BW)	Measured with a 10µF/25V X7R MLCC	3.3V, 5V Output Models		30		mVp-p	
	Measured with a 10µF/25V X7R MLCC	12V, 15V Output Models		40			
	Measured with a 4.7µF/50V X7R MLCC	24V Output Models		50			
Transient Response Recovery Time	25% load step change			250		µs	
Start-Up Time	Constant resistive load	Power Up		30		ms	
		Remote On/Off		30			
Temperature Coefficient			-0.02		+0.02	%/°C	
<b>PROTECTION</b>							
Short Circuit Protection			Continuous, automatic recovery				
Over Load Protection	% of rated Iout; hiccup mode			150		%	
Over Voltage Protection	Continuous clamp	Single Output Models	3.3V Output Models	3.7		5	VDC
			5V Output Models	5.6		7.0	
			12V Output Models	13.5		16	
			15V Outputs Models	18.3		22.0	
		Dual Output Models	24V Output Models	29.1		34.5	
			5V Output Models	5.6		7.0	
			12V Output Models	13.5		18.2	
			15V Outputs Models	17.0		22.0	
<b>GENERAL SPECIFICATIONS</b>							
Efficiency	Nominal input voltage and full load		See Table				
Switching Frequency			225	250	275	kHz	
Isolation Voltage	1 minute	Input to Output	5000			VAC	
Isolation Capacitance				12	17	pF	
Leakage Current	240VAC, 60Hz				2	µA	
Clearance/Creepage			8			mm	

**TECHNICAL SPECIFICATIONS: DCMPPW06 SERIES**

All specifications are based on 25°C, Nominal Input Voltage, and Maximum Output Current unless otherwise noted.  
 We reserve the right to change specifications based on technological advances.

SPECIFICATION	TEST CONDITIONS	Min	Typ	Max	Unit
<b>ENVIRONMENTAL SPECIFICATIONS</b>					
Operating Ambient Temperature	Without derating	-40		+88	°C
	With derating	+88		+105	
Storage Temperature Range		-55		+125	°C
Thermal Impedance	Natural convection (20LFM)		18		°C/W
Relative Humidity		5		95	% RH
Thermal Shock		MIL-STD-810F			
Vibration		MIL-STD-810F			
MTBF	MIL-HDBK-217F Ta=25°C, Full Load	4,718,000			hours
<b>PHYSICAL SPECIFICATIONS</b>					
Weight		0.48oz (14g)			
Dimensions (L x W x H)		1.25x0.80x0.40 inches (31.8x20.3x10.2mm)			
Case Material		Non-conductive black plastic			
Base Material		Non-conductive black plastic			
Potting Material		Silicon (UL94-V0)			
<b>SAFETY &amp; EMC CHARACTERISTICS</b>					
Safety Approvals (pending)	ANSI/AAMI ES60601-1, IEC60601-1, EN60601-1, UL60950-1 <sup>(6)</sup> , EN60950-1, IEC60950-1				
EMI (See Note 2)	EN55011, EN55022, and FCC Part 18				Class A
ESD	EN61000-4-2	Air ±8kV Contact ±6kV		Perf. Criteria A	
Radiated Immunity	EN61000-4-3	10 V/m		Perf. Criteria A	
Fast Transient (See Note 3)	EN61000-4-4	±2kV		Perf. Criteria A	
Surge (See Note 3)	EN61000-4-5	±2kV		Perf. Criteria A	
Conducted Immunity	EN61000-4-6	10 Vrms		Perf. Criteria A	
Power Frequency Magnetic Field	EN61000-4-8	100A/m continuous; 1000A/m 1 second		Perf. Criteria A	




**NOTES**

- The "x" in the model number represents the Pin Connection type. It can be "A" for pin connection type A or "B" for pin connection type B. See mechanical drawings on page 4 for more information.
- The DCMPPW06 series meets EMI Class A without an external filter added. This series can only meet EMI Class B with external components added. Please contact factory for more information.
- An external input filter capacitor is required if the module has to meet EN61000-4-4, EN61000-4-5.
  - For 24VDC nominal input models we recommend connecting an aluminum electrolytic capacitor (Nippon Chemi-con KY series, 470µF/50V) in parallel.
  - For 48VDC nominal input models we recommend connecting an aluminum electrolytic capacitor (Nippon Chemi-con KY series, 330µF/100V) in parallel.
- Remote ON/OFF control is optional and is only available for "B" type pin connection models. To order the converter with remote ON/OFF add the suffix "-P" to the model number (Ex: DCMPPW06-48S12B-P).
- Trim function is optional and is only available for "B" type pin connection models. To order the converter with Trim pin add the suffix "-T" to the model number (Ex: DCMPPW06-48S12B-T).
- This product is Listed to applicable standards and requirements by UL.

**CAUTION:** This power module is not internally fused. An input line fuse must always be used.


\*Due to advances in technology, specifications subject to change without notice.

**CHARACTERISTIC CURVES**



**MECHANICAL DRAWINGS**


**A Type Pin Connection (Suffix "A")**



PIN CONNECTIONS		
PIN	SINGLE	DUAL
1	+INPUT	+INPUT
11	NO PIN	COMMON
12	-OUTPUT	NO PIN
13	+OUTPUT	-OUTPUT
15	NO P IN	+OUTPUT
23	-INPUT	-INPUT
24	-INPUT	-INPUT

1. Dimensions in inch (mm)
2. Tolerance:  $x.xx \pm 0.02$  ( $x.x \pm 0.5$ )  
 $x.xxx \pm 0.01$  ( $x.xx \pm 0.25$ )
3. Pin Pitch Tolerance:  $\pm 0.01$  ( $\pm 0.25$ )
4. Pin Dimension Tolerance:  $\pm 0.004$  ( $\pm 0.1$ )

**B Type Pin Connection (Suffix "B")**




PIN CONNECTIONS		
PIN	SINGLE	DUAL
1	CTRL (Optional)	CTRL (Optional)
2	-INPUT	-INPUT
10	TRIM (Optional)	TRIM (Optional)
11	**NO PIN/NC	-OUTPUT
14	+OUTPUT	+OUTPUT
16	-OUTPUT	COMMON
22	+INPUT	+INPUT
23	+INPUT	+INPUT

\*\* : For Single Output Models Pin 11 is "NO PIN" with the Trim pin option (Suffix "-T") and "NC" without the trim pin option.

1. Dimensions in inch (mm)
2. Tolerance:  $x.xx \pm 0.02$  ( $x.x \pm 0.5$ )  
 $x.xxx \pm 0.01$  ( $x.xx \pm 0.25$ )
3. Pin Pitch Tolerance:  $\pm 0.01$  ( $\pm 0.25$ )
4. Pin Dimension Tolerance:  $\pm 0.004$  ( $\pm 0.1$ )

**External Output Trimming**

Output can be externally trimmed by using the method shown below. ( ) for dual output trim.



**MODEL NUMBER SETUP**

DCMPPW	06	-	48	S	05	B	-	P <sup>(1)</sup>	T <sup>(1)</sup>
Series Name	Output Power		Input Voltage	Output Quantity	Output Voltage	Pin Connection		Remote ON/OFF Option	Trim Option
	<b>06:</b> 6 Watts		<b>24:</b> 24 VDC <b>48:</b> 48 VDC	<b>S:</b> Single Output  <b>D:</b> Dual Output	<b>33:</b> 3.3 VDC <b>05:</b> 5 VDC <b>12:</b> 12 VDC <b>15:</b> 15 VDC <b>24:</b> 24 VDC  <b>05:</b> ±5 VDC <b>12:</b> ±12 VDC <b>15:</b> ±15 VDC	<b>A:</b> A Type <b>B:</b> B Type		<b>None:</b> No Remote ON/OFF <b>P:</b> Remote ON/OFF	<b>None:</b> No Trim <b>T:</b> Trim

(1) Remote ON/OFF Control and Trim options are only available for “B” type pin connection models.

**COMPANY INFORMATION**

Wall Industries, Inc. has created custom and modified units for over 50 years. Our in-house research and development engineers will provide a solution that exceeds your performance requirements on-time and on budget. Our ISO9001 certification is just one example of our commitment to producing a high quality, well-documented product for our customers.

Our past projects demonstrate our commitment to you, our customer. Wall Industries, Inc. has a reputation for working closely with its customers to ensure each solution meets or exceeds form, fit and function requirements. We will continue to provide ongoing support for your project above and beyond the design and production phases. Give us a call today to discuss your future projects.

Contact **Wall Industries** for further information:

Phone: ☎(603)778-2300  
 Toll Free: ☎(888)597-9255  
 Fax: ☎(603)778-9797  
 E-mail: [sales@wallindustries.com](mailto:sales@wallindustries.com)  
 Web: [www.wallindustries.com](http://www.wallindustries.com)  
 Address: 37 Industrial Drive  
 Exeter, NH 03833

©2019 Wall Industries, Inc. Specifications subject to change without notice. Wall Industries is not responsible for typographical errors. The information contained herein is for informational purposes only. This information is provided by Wall Industries and we make no representations or warranties of any kind, express or implied, about the completeness, accuracy, reliability, suitability or availability with respect to the information contained in this document for any purpose. All product and manufacturer names are trademarks or registered trademarks of their respective companies.