



AC/DC Power Supplies DC/DC Converters

Standard, Modified & Custom Solutions



MEDICAL



MILITARY



RAILWAY



LIGHTING



INDUSTRIAL



VEHICLE



ROBOTICS



EV

Request a Hard Copy
of the Brochure

WALL[®]
Wall Industries, Inc.

AC/DC Supplies



MEDICAL



MILITARY



RAILWAY



LIGHTING



INDUSTRIAL



VEHICLE



ROBOTICS



LEVEL VI



EV



HI ISOLATION

ENCLOSED CASE

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
PSHF	35W	33.6~36W	170~264	S	5, 12, 15, 24, 48	-20~70°C	3.88 x 3.23 x 1.38in	-
	100W	100~108W	85~132/170~264	S	5, 7.5, 12, 13.8, 15, 24, 48	-10~50°C	7.83 x 3.86 x 1.54in	-
	240W	200~240W	85~132/170~264	S	5, 7.5, 12, 15, 24, 30, 48	-10~50°C	7.83 x 4.33 x 1.97in	-
PSSEU	60	48.1~63W	90~264	S, D, T, M	-5, -10, -12, -15, -24, 3.3, 5, 10, 12, 15, 24, 28, 35, 36, 48, 3~5, 5~6, 6~8, 8~11, 11~13, 13~16, 16~21, 21~27, 27~33, 33~40, 40~50	0~70°C	5.43 x 3.43 x 1.76in	-
PSPFE	480	516~528W	85~264	S	12, 15, 24, 48	-20~70°C	10.94 x 5 x 1.69in	-

DIN RAIL

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
PSDG	-75	75W	84~264	S	12, 24	-25~70°C	4.69 x 1.26 x 4.88in	-
	-120	120W	85~264	S	12, 24, 48	-25~70°C	4.69 x 1.26 x 4.88in	-
	-240	240W	85~264	S	24, 48	-25~70°C	4.69 x 1.77 x 4.88in	-
	-480	480W	85~264	S	24, 48	-25~70°C	4.79 x 2.76 x 4.88in	-

OPEN FRAME

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
PSH	F15W	15~15.6W	85~264	S	5, 12, 15, 24, 48	-10~50°C	3.94 x 1.82 x 0.87in	-
PSMBU	31	30W	80~275	S	5, 7, 9, 12, 15, 18, 24, 30, 36	-10~70°C	4 x 1.99 x 1.16in	
	81	70~80W	90~260	S	5, 7, 9, 12, 15, 18, 24, 30, 36	0~70°C	5 x 3.01 x 1.11in	
	123	123~125W	90~260	D	5, 12, 19, 24, 36, 48	-10~70°C	6 x 3.5 x 1.46in	
PSHBU	58	33~60W	80~275	S	5~6, 6~8, 8~11, 11~13, 13~16, 16~21, 21~27, 27~33, 33~40, 40~50, 50~55	-10~70°C	4 x 1.5 x 1.04in	
PSSNP	-Y04	45W	90~264	S, D, T	-12, 3.3, 5, 12, 15, 24, 48	0~70°C	3.98 x 2 x 1.10in	
PSEPM	1200	100~200W	90~264	S, D, T, M	-12, 5, 9, 10, 11, 12, 15, 16, 17, 18, 19, 22, 23, 24, 34, 35, 36, 46, 47, 48, 54, 55, 56	0~50°C	5 x 3 x 1.5in	
PSIAC	450	450W	85~264	S	12, 15, 24, 28, 48, 53	-40~85°C	5 x 3 x 1.58in	

CHASSIS MOUNT

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
PSAKF	-	14~15W	85~265	S, D, T	-12, -15, 5, 12, 15, 24, 48	-25~71°C	3.81 x 2.13 x 0.92in	-
PSLH	-	4~26.4W	85~305	S	3.3, 5, 9, 12, 15, 24, 48	-40~70°C	3.78 x 2.13 x 1.16/1.25in 3.90 x 2.13 x 1.16/1.25in	-
PSAJM24	-	24W	85~264	S, D	-15, -12, 5, 9, 12, 15, 24	-40~80°C	3.78 x 2.13 x 0.92in	

AC/DC Supplies



MEDICAL



MILITARY



RAILWAY



LIGHTING



INDUSTRIAL



VEHICLE



ROBOTICS



LEVEL VI



EV



HI ISOLATION

PCB MOUNT

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
PSA	ZC	2W	90~305	S	3.3, 5, 9, 12, 15, 24	-40~80°C	1.12 x 1.02 x 0.67in	-
	DF	4.62~7W	85~265	S	3.3, 5, 12, 15, 24	-25~71°C	2 x 1 x 0.76in	-
	HF	6.6~10W	85~265	S, D	-12, -15, 3.3, 5, 12, 15, 24	-25~71°C	2.52 x 1.77 x 0.75in	-
	KC	14.85~20W	90~264	S, D, T	-5, -12, -15, 3.3, 5, 7.35, 9, 12, 15, 24	-25~70°C	2.76 x 1.89 x 0.87in	-
	JC	26.4~40W	90~264	S, D, T	-5, -12, -15, 3.3, 5, 5.1, 9, 12, 15, 24	-40~70°C	3.5 x 2.5 x 0.98in	-
	QC125	125W	90~264	S	12, 15, 24, 48	-25~70°C	5.83 x 2.80 x 1.50in	-

DESKTOP

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
DT	24	15~24W	90~264	S	5, 9, 12, 16, 18, 24, 36, 48	-20~40°C	3.07 x 1.97 x 1.38in	
DTA	-065A3	40~65W	90~264	S	5, 8, 12, 15, 19, 24, 36, 48	0~70°C	5.2 x 2.72 x 1.57in	
DTEA	1024	16~36W	100~240	S	5~8, 9~11, 12, 12~17, 18~24, 24, 36~48	0~40°C	3.86 x 1.79 x 1.23in	
	1101	80~130W	100~240	S	12~16, 19~24, 48~56	0~40°C	5.39 x 2.32 x 1.34in	
	1250	160~250W	100~240	S	12~18, 19~28, 32~42, 44~56	0~40°C	7.17 x 3.33 x 1.81in	
DTEM	1068	25~72W	100~240	S	5~9, 12~16, 18~24, 32~42, 44~56	0~40°C	4.45 x 1.93 x 1.38in	
	1300	230~310W	100~240	S	12~18, 19~28, 32~42, 44~56	0~40°C	7.78 x 4.02 x 2.01in	

WALL MOUNT

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
WMSAW	06D	1.8~6W	90~264	S	5, 6, 9, 12, 24	10~40°C	1.52 x 0.93 x 1.65in	
	14	7.5~15W	90~264	S	5, 7.5, 9, 12, 15, 24	10~40°C	2.92 x 1.15 x 1.64in	
WMEM	1019	15~24W	100~240	S	5~8, 9~13, 14~19, 20~27, 28~35, 36~48	0~40°C	2.36 x 1.54 x 1.02in 2.62 x 1.02 x 1.79in	
	1036	15~36W	100~240	S	9~15	0~50°C	3.92 x 1.79 x 1.22in	
WMGPSU	40	25~40.6W	100~240	S	5~6, 6~8, 8~11, 11~13, 13~16, 16~21, 21~27, 27~33, 33~58	0~40°C	2.97 x 1.26~1.92 x 1.87in	
	60	30~60.32W	100~240	S	5~6, 6~8, 8~11, 11~13, 13~16, 16~21, 21~27, 27~33, 33~58	0~40°C	3.68 x 1.38 x 2.02~2.36in	

LED

Series Name	Series Suffix	Watts	Input Voltage Range (VAC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
PSHL	20	20W	90~264	S	12, 24, 36, 48	-30~50°C	5.83 x 1.57 x 1.18in	
PSLSU	60	60W	90~305	S	11~13, 16~21, 21~27, 40~50, 50~58	-20~70°C	6.61 x 1.67 x 1.22in	
	85	85W	90~305	S	21~27, 27~33, 33~40, 40~50	-20~70°C	6.81 x 1.94 x 1.36in	
	120	120W	90~305	S	21~27, 27~33, 33~40, 40~50	-20~70°C	7.87~8.66 x 1.94 x 1.36in	

DC/DC Supplies



MEDICAL



MILITARY



RAILWAY



LIGHTING



INDUSTRIAL



VEHICLE



ROBOTICS



LEVEL VI



EV



HI ISOLATION

CHASSIS MOUNT

Series Name	Series Suffix	Watts	Input Voltage Range (VDC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
DCHF	10W	10~16.2W	10~18, 18~36, 36~72, 72~144	S, D	5, 12, 24	-20~50°C	3.94 x 2.83 x 1.22in	-
	20W	20~36.5W		S, D, T	-15, -12, 5, 12, 15, 24	-10~50°C	4.37 x 3.07 x 1.42in	-
	30W	30~41.5W		S, D, T	-15, -12, 5, 12, 24	-10~50°C	5.08 x 3.86 x 1.57in	-
	50W	50~67.5W		S, D, T	-15, -12, 5, 12, 15, 24	-10~50°C	6.30 x 3.86 x 1.54in	-
	40W	38.4~52.5W	18~36, 36~72, 72~144	S, D, T	-15, -12, 5, 12, 15, 24	-10~50°C	5.08 x 3.86 x 1.57in	-
	60W	60~62.4W		S	5, 12, 24, 48	-10~50°C	6.30 x 3.86 x 1.54in	-
	70W	70.5~72W		S	12, 15, 24, 48	-10~50°C	6.30 x 3.86 x 1.54in	-
	100W	100W		S	5, 12, 24, 48	-10~50°C	7.83 x 3.86 x 1.54in	-
	150W	148.8~151.2W		S	12, 24, 48	-20~50°C	7.83 x 3.86 x 1.97in	-
	350	330~350W	19~36, 36~72, 72~144	S	12, 24	-10~50°C	8.46 x 4.53 x 1.97in	-
	500	480~504W	19~72, 72~144	S	12, 24	-10~50°C	8.46 x 4.53 x 1.97in	-
	300W	300~302.4W	18~36, 36~72, 72~144	S	12, 24, 48	-20~50°C	8.46 x 4.53 x 1.97in	-
	500W	504W	36~75, 72~144	S	12, 24, 48	-20~50°C	9.84 x 6.30 x 3.43in	-
	600W	600~624W	36~72, 72~144	S	24, 28, 48	-10~50°C	9.84 x 6.30 x 3.43in	-
	700W	696~720W		S	24, 28, 48	-10~50°C	9.84 x 6.30 x 3.43in	-
	800W	810~840W		S	24, 30, 48	-10~50°C	9.84 x 6.30 x 3.43in	-
	1000W	840~1008W	36~72, 95~132	S	24, 28, 48	-10~50°C	9.84 x 6.30 x 3.43in	-
CMD	D	46.2~60W	18~36, 36~75	S	3.3, 5, 12, 15	-40~50°C	4 x 2.25 x 0.81in	-
	B	12~40W	9~18, 18~36, 36~75	S	1.5, 1.8, 2.5, 3.3, 5, 12, 15	-40~85°C	4 x 2.25 x 0.81in	-
	M	13.2~15W		S	3.3, 5, 12, 15	-40~85°C	4 x 2.25 x 0.81in	-
	BW	33~40W	9~36, 18~75	S	3.3, 5, 12, 15	-40~105°C	4 x 2.25 x 0.81in	-
	MW	9.9~15.3W		S	3.3, 5, 5.1, 12, 15	-40~60°C	4 x 2.25 x 0.81in	-

SURFACE MOUNT

Series Name	Series Suffix	Watts	Input Voltage Range (VDC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
DC	-	8~20W	36~75	S	2, 3.3, 5, 12, 15	-40~85°C	1.95 x 1.19 x 0.38in	-
DCMSAU	1	1W	4.5~5.5, 10.8~13.2, 21.6~26.4	S, D	±5, ±12, ±15, 5, 12, 15	-40~85°C	0.60 x 0.31 x 0.27in	-
	2	2W		S, D	±5, ±12, ±15, 5, 12	-40~85°C	0.50~0.60 x 0.37 x 0.34in	-
RG	W2	1.65~2W	4.5~9, 9~18, 18~36, 36~75	S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15	-40~85°C	0.74 x 0.50 x 0.33in	HI
	W3	2.3~3W		S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15	-40~71°C	0.74 x 0.50 x 0.33in	HI
	UW2	1.65~2W	4.5~18, 9~36, 18~75	S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15	-40~85°C	0.74 x 0.50 x 0.33in	HI
	UW3	2.3~3W		S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15	-40~71°C	0.74 x 0.50 x 0.33in	HI
RBA	1	1W	2.97~3.63, 4.5~5.5, 10.8~13.2, 13.5~16.5, 21.6~26.4	S	3.3, 5, 9, 12, 15, 24	-40~105°C	0.46 x 0.24 x 0.4in	HI
	X1	1W		S	3.3, 5, 6, 9, 12, 15, 24	-40~105°C	0.5 x 0.44 x 0.29in	HI

DC/DC Supplies



MEDICAL



MILITARY



RAILWAY



LIGHTING



INDUSTRIAL



VEHICLE



ROBOTICS



LEVEL VI



EV



HI ISOLATION

THROUGH HOLE

Series Name	Series Suffix	Watts	Input Voltage Range (VDC)	No. of Outputs	Output Range (VDC)	Temp. Range	Dimensions	Industry
LANE	-C	0.5~1W	4.5~5, 10.8~13.2, 13.5~16.5, 21.6~26.4	S	5, 9, 12, 12.75, 15	-40~85°C	0.77 x 0.24~0.28 x 0.39in	-
	-6KV	1W	4.5~5.5, 10.8~13.2	S, D	±5, ±12, ±15, 5, 12, 15	-25~85°C	0.87 x 0.30 x 0.49in	HI +
	H	1W	3.14~3.47, 4.75~5.25, 8.55~9.45, 11.4~12.6, 14.25~15.75, 22.8~25.2, 45.6~50.4	S, D	±3.3, ±5, ±9, ±12, ±15, ±24, 3.3, 5, 9, 12, 15, 24	-40~85°C	0.77 x 0.24~0.30 x 0.39in	HI
	2	2W	4.5~5.5, 8.1~9.9, 10.8~13.2, 13.5~16.5, 21.6~26.4	S, D	±5, ±9, ±12, ±15, ±24, 5, 9, 12, 15, 24	-40~85°C	0.77 x 0.24~0.28 x 0.39in	-
	H2	2W	3.14~3.47, 4.75~5.25, 11.4~12.6, 14.25~15.75, 22.8~25.2, 45.6~50.4	S, D	±5, ±9, ±12, ±15, 5, 9, 12, 15	0~70°C, -40~85°C	0.77 x 0.28 x 0.39in	-
	W	1.65~2W	4.5~9, 9~18, 18~36, 36~75	S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15	-40~85°C	0.86 x 0.36 x 0.44in	-
	UW2H	1.65~2W	9~36, 18~72	S, D	±5, ±9, ±12, ±15, 3.3, 5, 9, 12, 15	-40~85°C	0.86 x 0.36 x 0.44in	HI
	W3 H	2.3~3W	4.5~9, 9~18, 18~36, 36~75	S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15	-40~71°C	0.86 x 0.36 x 0.44in	HI
	UW3	2.3~3W	4.5~18, 9~36, 18~75	S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15	-40~71°C	0.86 x 0.36 x 0.44in	HI
RBA	T1	1W	4.5~5.5	S	3.3, 5, 9, 12, 15, 24	-40~105°C	0.46 x 0.24 x 0.4in	
	6	6W	9~18, 18~36, 36~75	S, D	±5, ±12, ±15, 3.3, 5, 9, 12, 15, 24	-40~85°C	1 x 1 x 0.46in	
	30	30W	9~36, 18~75	S, D	±5, ±12, ±15, ±24, 3.3, 5, 9, 12, 15, 24	-40~80°C	2 x 1 x 0.47in	
DCHB	W75	66~76.8W	9~36, 18~75, 43~160	S	3.3, 5, 12, 15, 24, 28, 48	-40~105°C	2.4 x 2.28 x 0.5in	★
	W100	82.5~100.8W	8.5~36, 9~36 16.5~75, 43~160	S	3.3, 5, 12, 15, 24, 28, 48	-40~115°C	2.4 x 2.28 x 0.5in	★
	W150	132~182.4W		S	3.3, 5, 12, 15, 24, 28, 48	-40~115°C	2.4 x 2.28 x 0.5in	★
	W200	165~240W		S	3.3, 5, 12, 15, 24, 28, 48	-40~115°C	2.4 x 2.28 x 0.5in	★
	150	132~196W	8.5/9~22, 16.5~36, 33~75	S	3.3, 5, 12, 15, 24, 28, 48, 53	-40~115°C	2.4 x 2.28 x 0.5in	★
	200	165~255W	8.5/9~22, 16.5~36, 33~75	S	3.3, 5, 12, 15, 24, 28, 48, 53	-40~115°C	2.4 x 2.28 x 0.5in	★
	500	500W	18~36, 200~400	S	5, 6.5, 12, 24, 28, 36, 48	-40~100°C, -55~100°C	2.28 x 2.4 x 0.5in	HI
JFC	W	13.2~15.6W	9~36, 18~75	S, D	±5, ±12, ±15, ±24, 3.3, 5, 12, 15, 24	-40~60°C	1 x 1 x 0.39in	-
	W10	9.9~10W	9~36, 18~75	S, D	±5, ±12, ±15, 3.3, 5, 12, 15, 24	-40~85°C	1 x 1 x 0.39in	
	W20	14.85~20W		S, D	±12, ±15, ±24, 3.3, 5, 12, 15, 24	-40~101°C	1 x 1 x 0.39in	-
	W30	23.1~30W		S, D	±12, ±15, ±24, 3.3, 5, 12, 15, 24	-40~50°C	1 x 1 x 0.39in	-
	10	9.9~10W	9~18, 18~36, 36~75	S, D	±5, ±12, ±15, 3.3, 5, 12, 15, 24	-40~85°C	1 x 1 x 0.39in	
	20	14.85~20W		S, D	±12, ±15, ±24, 3.3, 5, 12, 15, 24	-40~60°C	1 x 1 x 0.39in	
	30	23.1~30W		S, D	±12, ±15, ±24, 3.3, 5, 12, 15, 24	-40~50°C	1 x 1 x 0.39in	
DBW	-	33~40	9~36, 18~75	S, D	±12, ±15, 3.3, 5, 12, 15	-40~50°C	2 x 2 x 0.40in	-
FA	-	250~300	10~36	S	5, 12, 15, 20, 24, 26, 28, 43, 48	-40~100°C	4.6 x 2.4 x 0.5in	★
HP	-	600W	10~36	S	12, 15, 20, 24, 26, 28, 48	-40~100°C	6 x 3 x 0.69in	★

Custom Capabilities

*Fully Custom Power Design Capabilities
Backed by our In-House Engineering Team*

8-Step Design Process



ADVANCED TESTING & VERIFICATION EQUIPMENT

- Environmental Chambers for Temperature & Life Testing
- MYDATA SMT Component Placement Machines
- MPM Stencil Printer
- Automated Optical Inspection System
- Heller Convection Reflow Oven
- Aqueous Technology Batch Cleaning Equipment
- Magnetic Coil Winding Department In-House
- HALT/HASS Testing Capabilities with Outside Partners

CUSTOMS DESIGN CERTIFICATIONS

- UL60601-1
- EN60601-1
- FCC Part 15, 18
- CISPR Specifications
- Mil-Std-704 Aircraft Power Standards
- Mil-Std-1399 Shipboard Standards
- Mil-Std-1275 Military Vehicle Standards
- Mil-Std-461 Electro Magnetic Emissions Requirements
- Mil-Std-217 MTBF Standards
- Mil-Std-810 Environmental Testing
- Contact Us for a Complete List

ADVANCED SOFTWARE

- P-Spice Simulation S0
- Solid Works
- PADS
- AutoCad
- ICAPS Circuit Simulation

Custom Projects

Custom Projects Across Any Industry

MILITARY



- 270 Watts
- Desktop Converter
- 90-264VAC
- FCC Part 15 Sub part B
- EN60950



- 750 Watts
- Battery Charger
- Mil 1275 Input
- Quick Charging to 12 & 25VDC Batteries



- 37 Watts
- 18-36VDC
- 3.3VDC @10A
- 300VDC @12A



- 160 Watts
- 13 Outputs
- EMI Compliant
- MIL Standard 461 and 801

MEDICAL



- 24VDC Charger
- EMI Compliant
- Mil 801, 704, and 1275
- Mil Standard 461 for Radiated and Conducted



- 2kw
- Multiple 24VDC Battery Charger Outputs
- EMI Compliant
- FCC part 15 Subpart B

INDUSTRIAL



- 1200 Watts
- 24VDC Output
- Liquid Cooled
- 100% EMI Agency Approved
- Current Controllable



- 1200 Watt Power Supplies in Parallel
- Packaged as 24VDC Out at 100amp unit
- Power Limiting Mode

OTHER

Wall Industries, Inc. offers fully custom power design capabilities. Our team of electrical and mechanical power design engineers will utilize proven design topologies and concepts to create a solution to your power requirements. We can provide a high-quality, innovative, solution for any design requirement, just give us a challenge and we will be able to solve it. Contact the factory if you have a custom solution you are ready for us take on.

What We Offer

R&D

- P-Spice Simulation Software, PADS, AUTOCAD, and Solidworks
- Environmental Chambers for Life and Temperature Testing
- HALT/HASS Testing Capabilities with partners
- Limited In-House EMI and EMC Testing Capabilities
- Engineering Team Provides Analog, Digital, Mechanical, and Packaging Expertise to Assist with Design Needs

Quality Assurance

- In-Process Inspection
- ISO9001 Quality System In Place
- Certifications and Standards Include ISO, IPC, HALT, SPC, UL, EN
- 100% Final Electrical Hi-Pot Testing
- Employees certified and trained to PC-610 Workmanship Standards
- Extensive Burn-In Capability, Standard, or Customer Specific
- 100% Final Electric and Hi-Pot Testing

About Wall

- Incorporated in 1960
- ISO Registered with UL, file #10002324
- Supplier of the Year Awards from World Class Customers
- One of the World Trade Magazine's top "100 Fast-Growing High Tech Manufacturers"
- Representative Network through North America for Convenient Assistance
- In-House Design Engineering Team

Certifications



www.wallindustries.com



(603) 778-2300



sales@wallindustries.com

37 Industrial Drive, Exeter, NH 03833

WALL[®]
Wall Industries, Inc.